

# ARAFLON 4666 EXPANDED PTFE GASKET TAPE

A self-adhesive tape made from 100% pure ePTFE

Softer and more flexible PTFE suitable for irregular and rough surfaces sealings. Wherever an irregular sealing surface and standard gaskets cannot be used, Araflon 4666 gasket tape can be applied with user friendly and easy installation methods. This is easy to compress and exhibits excellent resistance to creep and cold flow.

Applications:



## Recommended for

Chemical Industry  
 Petrochemical and process industries  
 Pharmaceutical, paper, pulp, food beverage industries  
 Flange connections, normal and irregular  
 Reactor and process vessels and exchangers  
 Food Industry  
 Mining Industry

## Avoid

Molten Alkali  
 Hydrofluoric Acids  
 Fluorine gas

## Operating Conditions

Minimum Temperature	(°C/°F)	-268/-450
Maximum Temperature	(°C/°F)	260/500
Short Term Peak	(°C/°F)	315/600
Pressure	(bar/psi)	200/2900

## Physical Properties

Color	White
Density	0.8gm/cm <sup>3</sup>
pH	0-14
Size Range	7mm Width to 25mm Width & 2.5mm Thk to 7mm Thk

The data we are herewith providing are all based on laboratory testing and are proposed to technical designers as possible and useful advice.

Deviations from the values hereabove indicated may occur, but they do not constitute themselves either detriment of quality or reason for rejection.